

Destacker, PCB Loader / LP Entstapler

- Bare board loader
Rohleiterplatten-Entstapler
- SMEMA INPUT for Pass-mode and OUTPUT
SMEMA Einlauf für Durchfahrbetrieb und Auslauf



PCB Dimension [mm] / LP-Abmaße		Option
Length	100-420 Pass 447	535
Width	70 - 410	70 - 460
Thickness	0,8 - 2,0	
height top	50	
height bottom	30	
PCB -Edge	3	
Transport height	950 +/-45	

Machine Dim. [mm] / Masch.-Abmaße		Option
Length (front)	600	
Width (depth)	760	
Height	1050	
Weight	110 kg	

Materials / Material		Option
Main Structure	Sheet metal	
Color	RAL 7035	
Transp. Sheet	No / Nein	

Belt conveyor / Förderband		Option
DC-Motor	Speed-regulator seperate in/out	
Belt	flat, antistatic	

Stack / Stapel		Option
Qty. Stack	1	

PCB Capacity / LP Kapazität		Option
Qty. Conv.	1	
Qty. Rack	up to 250	

Operator panel / Bedienung		Option
HMI panel	Push button Light-Switch	Display

Supply and Connections / Anschlüsse		Option
Voltage	230V 1L N PE 50Hz	
Power	70 W	
Interface	SMEMA	add. / others
Air pressure / Druckluft	0,5 MPa	

Width adjustment / Breitenverstellung		Option
Belt	manual	automatic

PLC / SPS		Option
System	Siemens S7-xxx	Line PC Network

Miscellaneous / Sonstiges		Option
Buzzer / Ton	Yes / Ja	
Destack mechanic	Pneumatic	

Additional Options / zusätzliche Optionen:

- | | |
|--|--|
| <ul style="list-style-type: none"> - Transport flow direction from right to left - Additional Board sensor - Ultrasonic Board sensor - Signal light tower 1 lamp - Signal light tower 2 lamps | <ul style="list-style-type: none"> - Machine extension - add. belt conveyor - Automatic width adjustment for extension - Additional Safety / Interlock switch - Stopper - Safety panel and safety switch rail |
|--|--|

Functional principle, layout dimensions Funktionsprinzip, Grundriss Abmaße

- PCB transport via belt conveyor (Pass mode)
LP Transport mit Förderbändern (Durchlaufbetrieb)
- Pneumatic PCB separator
Pneumatische LP-Vereinzelung

